



P/N LEGEND

<u>A2502</u> <u>WVB</u> - <u>XP</u> <u>N</u> <u>L</u> <u>N</u> <u>T1</u> <u>N</u> <u>K0</u> <u>G</u>									
①	②	③	④	⑤	⑥	⑦	⑧	⑨	⑩
① Series No.	② Connector type: WVB=Vertical B Type	③ No. of circuits	④ N=Halogen Free	⑤ Material: L=LCP	⑥ Color: N=Natural (Beige)	⑦ Plating code for contacts: T1=Matte Tin-plated	⑧ Plating code: N=Non-plating	⑨ Option code: K0=With pin kink	⑩ Packing code: G=Bag

SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass

Circuit No.	Dimensions			Circuit No.	Dimensions		
	A	B	C		A	B	C
02P	2.50	7.50	6.70	09P	20.00	25.00	24.20
03P	5.00	10.00	9.20	10P	22.50	27.50	26.70
04P	7.50	12.50	11.70	11P	25.00	30.00	29.20
05P	10.00	15.00	14.20	12P	27.50	32.50	31.70
06P	12.50	17.50	16.70	13P	30.00	35.00	34.20
07P	15.00	20.00	19.20	14P	32.50	37.50	36.70
08P	17.50	22.50	21.70	15P	35.00	40.00	39.20

				燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.			
UNIT		SCALE	SHEET	TITLE:			
mm		1 : 1	1 of 1	2.50mm PITCH 180° WAFER			
DRAWN BY		APPROVED BY					
陳彥兆		董正一					
2012.11.26		2012.11.26		DRAW NO. : A2502WVB-XPXXXXXXX			
GENERAL TOLERANCE				REV. A1			
A1	ENI310140353	2013.10.14	郭本恩	X.X±0.25	ANGLE±		
A0	NEW RELEASE	2012.11.26	陳彥兆	X.XX±0.15			
REV.	DESCRIPTION	DATE	NAME	X.XXX±0.05			