


TYPE 1



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 500MΩ Min
 Withstanding Voltage: 800V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-0
 Color: White

Ordering Information & Dimensions

| PART NO. | Dimensions | |
|---------------|------------|-------|
| | A | B |
| A2540WR-02PN1 | 2.50 | 5.00 |
| A2540WR-03PN1 | 5.00 | 7.50 |
| A2540WR-04PN1 | 7.50 | 10.00 |
| A2540WR-05PN1 | 10.00 | 12.50 |
| A2540WR-06PN1 | 12.50 | 15.00 |
| A2540WR-07PN1 | 15.00 | 17.50 |
| A2540WR-08PN1 | 17.50 | 20.00 |
| A2540WR-09PN1 | 20.00 | 22.50 |
| A2540WR-10PN1 | 22.50 | 25.00 |
| A2540WR-11PN1 | 25.00 | 27.50 |
| A2540WR-12PN1 | 27.50 | 30.00 |
| A2540WR-13PN1 | 30.00 | 32.50 |
| A2540WR-14PN1 | 32.50 | 35.00 |
| A2540WR-15PN1 | 35.00 | 37.50 |

| | | | | | | | |
|------|-------------|-------------------|--|-------------|-------|----------------------------|------------|
| | | | | UNIT | SCALE | SHEET | TITLE: |
| | | | | mm | | 1 of 1 | |
| | | DRAWN BY | | APPROVED BY | | DRAW NO. : A2540WR-XPNI | REV. AO |
| | | 歐陽小強 | | 謝瑞清 | | | |
| | | 2008.09.16 | | 2008.09.16 | | | |
| | | GENERAL TOLERANCE | | | | | |
| | | X. X±0.25 | | ANGLE± | | | |
| | | X. XX±0.15 | | | | | |
| | | X. XXX±0.05 | | | | | |
| A0 | NEW RELEASE | 2008.09.16 | | | | | |
| REV. | DESCRIPTION | DATE | | | | | |