



P/N LEGEND

<u>A3501</u>	<u>HMA-02P</u>	<u>N</u>	<u>0</u>	<u>W</u>	<u>NP</u>	<u>N</u>	<u>00</u>	<u>G</u>
①	②	③	④	⑤	⑥	⑦	⑧	⑨

① Series No.
 ② Connector type: HMA=Plug A Type
 ③ No. of circuits
 ④ N=Halogen Free
 ⑤ Material: 0=Nylon 66-V0
 ⑥ Color: W=White
 ⑦ Plating code: NP=Non-plating
 ⑧ Plating code: N=Non-plating
 ⑨ Option code: 00=Standard
 ⑩ Packing code: G=Bag

SPECIFICATIONS

Current Rating: 1A AC,DC
 Voltage Rating: 1400V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 3800V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Natural(White)

				燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.	
UNIT	SCALE	SHEET	TITLE:		
mm	1 : 1	1 of 1	3.50mm PITCH HOUSING WITH LOCK, ULTRA LOW PROFILE		
DRAWN BY 陳柏菘	APPROVED BY 董正一				
2010.11.24	2010.11.24		DRAW NO. : A3501HMA-02PNXXXXXXX		
GENERAL TOLERANCE			REV. A0		
A0	NEW RELEASE	2010.11.24	陳柏菘	ANGLE±	
REV.	DESCRIPTION	DATE	NAME	DRAW NO. : A3501HMA-02PNXXXXXXX	
				REV. A0	