



03P~12P

02P

P/N LEGEND

C3030 HF-XP N 0 X NP N 00 G
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨ ⑩

- ① Series No.
- ② Connector type: HF=Receptacle
- ③ No. of circuits
- ④ N=Halogen Free
- ⑤ Material: 0=Nylon 66-V0
- ⑥ Color: W=White R=Red B=Black
- ⑦ Plating code: NP=Non-plating
- ⑧ Plating code: N=Non-plating
- ⑨ Option code:
00=Standard
- ⑩ Packing code: G=Bag

SPECIFICATIONS

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: White Black or Red

Circuit No.	Dimensions	
	A	B
02P	3.00	6.80
03P	6.00	9.80
04P	9.00	12.80
05P	12.00	15.80
06P	15.00	18.80
07P	18.00	21.80
08P	21.00	24.80
09P	24.00	27.80
10P	27.00	30.80
11P	30.00	33.80
12P	33.00	36.80



燦達電子工業股份有限公司
 JOINT TECH ELECTRONIC IND. CO., LTD.

UNIT	SCALE	SHEET
mm	1 : 1	1 of 1
DRAWN BY 黄模有 2014.07.07		APPROVED BY 董正一 2014.07.07
GENERAL TOLERANCE		
A0	NEW RELEASE	2014.07.07
REV.	DESCRIPTION	DATE

TITLE:	
3.00mm PITCH HOUSING-RECEPTACLE, SINGLE ROW, MICRO-FIT	
DRAW NO. :	REV. A0

REV.	DESCRIPTION	DATE	NAME
A0	NEW RELEASE	2014.07.07	黄模有

X. X±0.25	ANGLE±
X. XX±0.15	
X. XXX±0.05	

DRAW NO. : C3030HF-XPNXXXXXXXX	
REV. A0	