


2X01P

SPECIFICATIONS

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
C3030HM-2X01P-V0	---	3.85
C3030HM-2X02P-V0	3.00	6.85
C3030HM-2X03P-V0	6.00	9.85
C3030HM-2X04P-V0	9.00	12.85
C3030HM-2X05P-V0	12.00	15.85
C3030HM-2X06P-V0	15.00	18.85
C3030HM-2X07P-V0	18.00	21.85
C3030HM-2X08P-V0	21.00	24.85
C3030HM-2X09P-V0	24.00	27.85
C3030HM-2X10P-V0	27.00	30.85
C3030HM-2X11P-V0	30.00	33.85
C3030HM-2X12P-V0	33.00	36.85

		 JOINT TECH ELECTRONIC IND. CO., LTD. JOY DAY INDUSTRIAL CO., LTD.	
UNIT	SCALE	SHEET	TITLE:
mm		1 of 1	3.00mm PITCH HOUSING-PLUG, MICRO-FIT
DRAWN BY	APPROVED BY		
李勤	董正一		
2005.12.14	2005.12.14		
GENERAL TOLERANCE			
A1	REVISE	2007.04.16	X. X±0.25
A0	NEW RELEASE	2005.12.14	X. XX±0.15
REV.	DESCRIPTION	DATE	X. XXX±0.05
			D
			Φ
DRAW NO. :			REV. A1
C3030HM-2XNP-V0			