



**SPECIFICATIONS**

Current Rating: 5A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 10mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Material: Nylon 66,UL94V-0  
 Color: Black

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
C3030HMA-2X01P-V0	---	3.85
C3030HMA-2X02P-V0	3.00	6.85
C3030HMA-2X03P-V0	6.00	9.85
C3030HMA-2X04P-V0	9.00	12.85
C3030HMA-2X05P-V0	12.00	15.85
C3030HMA-2X06P-V0	15.00	18.85
C3030HMA-2X07P-V0	18.00	21.85
C3030HMA-2X08P-V0	21.00	24.85
C3030HMA-2X09P-V0	24.00	27.85
C3030HMA-2X10P-V0	27.00	30.85
C3030HMA-2X11P-V0	30.00	33.85
C3030HMA-2X12P-V0	33.00	36.85

				<b>JOINT TECH ELECTRONIC IND. CO., LTD.</b> <b>JOY DAY INDUSTRIAL CO., LTD.</b>	
		UNIT	SCALE	SHEET	
		mm		1 of 1	
		DRAWN BY		APPROVED BY	
		李勤		董正一	
		2005.12.14		2005.12.14	
GENERAL TOLERANCE					
A1	REVISE	2008.12.30	X.X±0.25	ANGLE±	
A0	NEW RELEASE	2005.12.14	X.XX±0.15		
REV.	DESCRIPTION	DATE	X.XXX±0.05		
				TITLE:	
				<b>3.00mm PITCH HOUSING-PLUG, MICRO-FIT</b>	
				DRAW NO. :	
				C3030HMA-2XNP-V0	
				REV. A1	