


SEC:A-A





SEC:B-B

Ordering Information & Specifications

PART NO.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
C3030M-TPE	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Tin-plated	15,000pcs
C3030M-HPE	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Gold-flash	15,000pcs
C3030M-HPE-G1	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Gold-plated 15u"	15,000pcs
C3030M-HPE-G2	AWG#20-#24	1.85mm(max)	Phosphor Bronze	Gold-plated 30u"	15,000pcs

Note:E-Stamping before Tin-plated or Gold-plated

				 燦達電子工業股份有限公司 JOINT TECH ELECTRONIC IND. CO., LTD.		
		UNIT	SCALE	SHEET		TITLE:
		mm	1 : 1	1 of 1		
		DRAWN BY		APPROVED BY		3.00mm PITCH CRIMP TERMINAL-MALE, MICRO-FIT
		董正一		董正一		
		2001.02.01		2001.02.01		
GENERAL TOLERANCE						DRAW NO. : C3030M-XX
		X. X±0.25	ANGLE±			
B3	EN1108250370	2011.12.15	謝金發	X. XX±0.15		
REV.	DESCRIPTION	DATE	NAME	X. XXX±0.05		